UDC 621.548

R.K.Manatbayev^{1*}, A.M.Satymbekov^{2**}, A.K.Tulepbergenov³, Zh.R.Ualiev⁴

 ¹ Physico-Technical Faculty, al-Farabi Kazakh National University, Almaty, Kazakhstan
 ² Faculty of Mathematical and Mathematical, Abay Kazakh National Pedagogical University, Almaty, Kazakhstan
 ³ Faculty of Mechanic-Mathematical, al-Farabi Kazakh National University, Almaty, Kazakhstan
 ⁴ Faculty of Chemistry and Chemical Technology, al-Farabi Kazakh National University, Almaty, Kazakhstan

*E-mail:rustem1977@mail.ru

Development of numerical model of interaction of the wind turbine to darya with the wind stream in the u-v-p variables

Abstract. The use of natural eco-friendly energy, such as wind, due to the use of wind energy devices [1-3]. This thesis is a theoretical study of the interaction of the rotating turbine Darrieus-type H-rotor wind flow. The paper considers the interaction of a uniform wind flow with a rotating wind turbine Darrieus-type H-rotor, based on the Navier-Stokes equations, which is supplemented by members which take into account the lift and the drag force. The numerical solution of the equations in the variables u-v-p. The results obtained and the development of his methods of analysis will be useful for the design work for the creation of industrial designs windmill carousel. *Keywords:* modern wind turbine, vertical-axis, balanced profile, flow, numerical model, non-uniform grid,

Reywords: modern wind turbine, vertical-axis, balanced profile, flow, numerical model, non-uniform grid, calculation, izoline.

Introduction

Wind – an environmentally friendly source of energy! In all the developed countries of the world wind as an energy source, is beginning to play a significant role in their energy mix. Continuously expanding manufacturing and designing efficient wind turbines [1,3]. The territory of the Republic of Kazakhstan has enormous wind energy potential, which, of course, suggest a bright future for the application of wind power units in the country.

Realizing the importance of the wind industry in the Republic of many scientific groups and individuals with more enthusiasm (and in many cases their own) are studying the problems of wind power and achieve certain results (Almaty Institute of Power Engineering and Telecommunications, Kazakh National University named after al-Farabi, Kazakh Scientific Research Institute of Power Engineering, Farm Equipment, The Society Joint " Kazakh Scientific Research Institute «hydro unit» " JSC Asia Energy project installation and many others). Cost-effectiveness of modern wind turbines is determined by the utilization of wind energy per unit area of the surface swept by the propeller in the airflow. Therefore, their design refers to the category of the most high-tech industries, based on current knowledge of aerodynamics, the theory of machines, materials, etc.

Average wind-energy unit (WPU), Daria , invented by French engineer (naturalist) Darya in 1904, consists of a blade -type aircraft wings with symmetrical about the chord profile (max) , connecting vertical shaft rotation with working wings (also symmetric profile) extending parallel to the axis rotation. The plane of the wing span (max) is horizontal and lies in the plane of rotation. The main distinguishing feature: Darrieus wind turbine works not responding to the changing direction of the wind.

Method of research

The purpose of this paper is to examine the theoretical 2D simulation of wind turbine carousel allows you to determine the optimum parameters of the turbine (see Fig. 1). We consider the development of a mathematical model to study the interaction of wind turbines carousel "Daria" with fixed air flow [1-4].

Under the action of the wind flow on the blades appear lift and drag forces. The lifting force acts on the blade positively spinning rotor. And the power of resistance - negative. For efficient operation of the unit value of these forces depend on the parameter Z, called "rapidity of the unit."

Parameter rapidity of the wind wheel is defined as follows

$$Z = \frac{W_*}{u_*}$$

where , $u_{\infty-}$ flow rate , $W_* = \omega r_0$ – linear speed of the blade , ω – angular speed of rotation of the rotor, r_o – radius, the distance from the center of rotation of the shaft to the blade.





To determine the mass of these forces is first determined by the angle of attack α and attack speed \overline{W} , and the coefficients of lift and drag forces depends on the angle of attack (Fig. 2).

$$\left| \vec{W} \right| = \sqrt{\left(u \sin \theta - v \cos \theta \right)^2 +} + \left(r_0 \omega + u \cos \theta + v \sin \theta \right)^2}, \quad (1)$$

$$u \sin \theta - v \cos \theta$$

$$tg\alpha = \frac{1}{r_0\omega + u\cos\theta + v\sin\theta}.$$

Introducing the local number of rapidity $Z = \frac{r_o \omega}{u_\infty}$, obtain,

$$\alpha = \arctan\left(\frac{u\sin\theta - v\cos\theta}{Z + u\cos\theta + v\sin\theta}\right)$$
(2)



Figure 2.

International Journal of mathematics and physics 4, No2 (2013)



Figure 3.

Determining the aerodynamic forces to introduce the unit vectors as shown in Figure 3: \vec{e}_w – resistance unit vector directed along the relative velocity vector, and \vec{e}_L – a unit vector directed perpendicular to lift it.

Elementary components of the aerodynamic forces:

a) lift pover of the profile:

$$\vec{R}_{L} = C_{L}(\alpha)\rho \frac{W^{2}}{2}h\vec{e}_{L}, \qquad (3)$$

where $C_L(\alpha)$ – lift coefficient, h – length of chord, b) the resistance force

$$\vec{R}_{\rm D} = C_{\rm D}(\alpha) \rho \frac{W^2}{2} h \vec{e}_{\rm W}, \qquad (4)$$

 $C_D(\alpha)$ – coefficient of drag force. Then calculated – R_x , R_y

$$R_{x} = \pi p_{Ox} \left(\vec{R}_{L} \right) + \pi p_{Ox} \left(\vec{R}_{D} \right)$$
$$R_{y} = \pi p_{Oy} \left(\vec{R}_{L} \right) + \pi p_{Oy} \left(\vec{R}_{D} \right)$$
(5)

A mathematical model of the impact of fixed air flow at a rate of "u" in the rotating wind turbine "Daria" is described by non-stationary Navier-Stokes and continuity equations and has the form:

$$\begin{cases} \frac{\partial \vec{\mathbf{V}}}{\partial t} + (\vec{\mathbf{V}} \nabla) \vec{\mathbf{V}} = -\nabla p + \nu \nabla^2 \vec{\mathbf{V}} + \vec{\mathbf{R}}, \\ \nabla \vec{\mathbf{V}} = 0. \end{cases}$$
(6)

The two-dimensional model of the task.

$$\begin{cases} \frac{\partial u}{\partial t} + u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y} = -\frac{\partial p}{\partial x} + v \left(\frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} \right) + R_x, \\ \frac{\partial v}{\partial t} + u \frac{\partial v}{\partial x} + v \frac{\partial v}{\partial y} = -\frac{\partial p}{\partial y} + v \left(\frac{\partial^2 v}{\partial x^2} + \frac{\partial^2 v}{\partial y^2} \right) + R_y, \\ \frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} = 0. \end{cases}$$
(7)

With the boundary conditions

$$u(x,0) = u(x,1) = u(0, y) = u_{\infty},$$

$$\frac{\partial u(1, y)}{\partial x} = 0;$$

$$v(x,0) = v(x,1) = v(0, y) = 0,$$
(8)

$$\frac{\partial v(1, y)}{\partial x} = 0.$$

As the aerodynamic resistance forces wind flow projections are taken averaged resistance forces and lift the blade (in the opposite direction) on the axis Ox and Oy in the form of point sources R_x , R_y and enter the right side of the equations of motion.

The numerical calculation of the Navie-Stokes equations is made in terms of velocity – pressure [4-9]. For easy calculation of the pressure field is used the idea of " artificial compressibility ", which is physically correct description of the interaction of the air flow with a rotating turbine (air – compressed gas). The essence of the idea is to introduce the continuity equation in the form of an additional term

$$\frac{\partial}{\partial t}\left(p+\frac{V^2}{2}\right).$$

The result is a modified system of equations of the form $(-\vec{r})$

$$\begin{cases} \frac{\partial \mathbf{V}}{\partial t} + (\vec{\mathbf{V}}\nabla)\vec{\mathbf{V}} = -\nabla \mathbf{p} + \mathbf{v}\nabla^{2}\vec{\mathbf{V}} + \vec{\mathbf{R}}, \\ \frac{\partial (\mathbf{p} + \mathbf{V}^{2}/2)}{\partial t} + \nabla\vec{\mathbf{V}} = 0, \\ \frac{\partial \mathbf{p}}{\partial t} + \nabla\vec{\mathbf{V}} = 0, \end{cases}$$
(9)

International Journal of mathematics and physics 4, №2 (2013)

for solutions that use different versions of the method of splitting. The basic idea of splitting is based on the method of particle-in-cell PIC. According to this scheme, first calculates the $\widetilde{\Xi}$

speed \vec{V} of the intermediate field equation

$$\frac{\widetilde{\vec{V}} - \vec{V}^n}{\tau} + (\vec{V}^n \nabla) \vec{V}^n = \nu \nabla^2 \vec{V}^n$$

(the value \vec{V}^n is assumed known). Then, this field tinker with the pressure gradient

$$\vec{\mathbf{V}}^{n+1} = \widetilde{\vec{\mathbf{V}}} - \tau \nabla \mathbf{p},$$

where p - stationary solution

$$\frac{\partial p}{\partial t} + \nabla \widetilde{\vec{V}} = \tau \nabla^2 p. \label{eq:varphi}$$

As a result of these steps is satisfied both equations (6).

In this problem, use the explicit scheme of splitting by physical factors. We introduce the following notation:

$$\nabla \times \vec{V} = \vec{\omega},$$

$$\nabla \vec{V} = D,$$
 (10)

$$\nabla \tilde{\vec{V}} = \widetilde{D}.$$

It is believed that at a time $t_n=n\tau$ (τ – time step, n – number of steps) are known, the velocity field \vec{V} and pressure p. Then, detection circuit unknown functions in time $t_n=(n+1)\tau$ can be represented as a three-stage splitting scheme:

1):
$$\begin{cases} \frac{\widetilde{\mathbf{u}} - \mathbf{u}^{n}}{\tau} = -\left(\mathbf{u}\frac{\partial \mathbf{u}}{\partial \mathbf{x}} + \mathbf{v}\frac{\partial \mathbf{u}}{\partial \mathbf{y}}\right) - \\ -\nu\left(\frac{\partial^{2}\mathbf{v}}{\partial \mathbf{y}\partial \mathbf{x}} - \frac{\partial^{2}\mathbf{u}}{\partial \mathbf{y}^{2}}\right) + \mathbf{R}_{x} \\ \frac{\widetilde{\mathbf{v}} - \mathbf{v}^{n}}{\tau} = -\left(\mathbf{u}\frac{\partial \mathbf{v}}{\partial \mathbf{x}} + \mathbf{v}\frac{\partial \mathbf{v}}{\partial \mathbf{y}}\right) - \\ -\nu\left(\frac{\partial^{2}\mathbf{v}}{\partial \mathbf{x}^{2}} - \frac{\partial^{2}\mathbf{u}}{\partial \mathbf{x}\partial \mathbf{y}}\right) + \mathbf{R}_{y} \end{cases}$$

2):
$$\nabla^2 p = -\frac{1}{\tau} \left(\frac{\partial \widetilde{u}}{\partial x} + \frac{\partial \widetilde{v}}{\partial y} \right);$$
 (12)

3):
$$\begin{cases} \frac{u^{n+1} - \widetilde{u}}{\tau} = -\frac{\partial p}{\partial x} \\ \frac{v^{n+1} - \widetilde{v}}{\tau} = -\frac{\partial p}{\partial y} \end{cases}$$
 (13)

Equation (12) is obtained by taking the divergence of both sides of (13) with the continuity equation (conditions solenoidality $div\vec{V}^{n+1} = 0$

The computational cycle is as follows: 1) – a known at the initial time of the velocity field of (11) is an intermediate velocity field, thereby determining the right side of equation (12), 2) – solved the Poisson equation (12) for the pressure; 3) – corrects the final (at this time layer) the field rate (13). The cycle is repeated until the execution of a test set or a specific point in time.

It uses a "checkerboard" grid, ie coordinates of the grid functions are separated in space.

This enables clearly interpret each cell as an element of protection which is characterized calculated pressure at its center $p_{i,j}$ and divergence D (according to the sign of the value D represents the occurrence of the source or drain in a given volume). Knowledge of the normal component of the velocity vector on the boundary of the cell allows you to calculate the flux of momentum (momentum per unit mass) over that boundary.

For this problem in a Cartesian coordinate system and an irregular grid two-dimensional finite difference scheme is as follows:

$$\begin{split} \widetilde{D}_{i,j} &= \frac{\widetilde{u}_{i,j} - \widetilde{u}_{i-1,j}}{\left(x_{i} - x_{i-1}\right)} + \frac{\widetilde{v}_{i,j} - \widetilde{v}_{i,j-1}}{\left(y_{j} - y_{j-1}\right)}; \\ D_{i,j}^{n+1} &= \frac{u_{i,j}^{n+1} - u_{i-1,j}^{n+1}}{\left(x_{i} - x_{i-1}\right)} + \frac{v_{i,j}^{n+1} - v_{i,j-1}^{n+1}}{\left(y_{j} - y_{j-1}\right)}. \end{split}$$

The result of the calculation of this problem is shown graphically in Figure 4. The results will be useful for engineers and designers in the design and manufacture of wind turbines with high technical and economic indicators.

International Journal of mathematics and physics 4, №2 (2013)



Figure 4.

Acknowledgements

This work was supported by grant funding research programs and projects of the Committee of Science RK, Grant number 1048/GF2. 2014.

References

1. Mei-Kao Liu, Mark A.Yocke, and Tomas

 C. Myers. Mathematical Model For the Analysis of Wind – Turbine Wakes // J. Energy. – 1983. – Vol.7. – № 1. – P.73-78.

2. Turyan C.J., Strickland J.H., Berg D.E. Moshnost vetroelektricheskih agregatov s vertikalnoi osiu vrashenia // Aerodinamicheskaia technical – $1988. - N_{\odot} 8. - p.105-121.$

3. Ershin A.K., Ershin Sh., Zhapbasbayev W.K. Osnovy teorii vetroturbuny Darye. – Almaty, 2001. – 104 p.

4. Loitsyansky L.G. Mechanica zhidkosti i gaza. –M.: Nauka. – 1987. – 904 p.

5. Batchelor J. Vvedenie v dinamiku jidkosti. – Moskva: Mir. – 1973. – 757 p..

6. Belotserkovskii O.M. Chislennoe modelirovanie v mechanice sploshnyh sred. – M.: Nauka. – 1994. – 519 p.

7. Marchuk G.I. Metody vychislennoi matematiki. M.Nauka. – 1980. – 535p.

8. Anderson D., Tannehill J. and Pletcher R. Vychislitelnaia gidromechanica I teploobmen. Izdatelstvo «Mir». – 1990. Vol. 1-2. – 720 p.

9. Roach P. Vychislitelnaia gidrodinamika. – Moskva: Mir. – 1980. – 616 p.